
906-0190A

GUN MOUNTS-









DESIGNING MANUFACTURING INSTALLATION

2011 DODGE CHARGER LAW ENFORCEMENT **PRODUCTS**

- 2011 Dodge Charger trunk drawer
- Full width trunk equipment tray made from 10-gauge aluminum that slides out for easy equipment placement and maintenance
- Spare tire must be removed or relocated to trunk floor
- Front is protected with a perforated aluminum panel





PDU42WB

- Organizes vehicle wiring runs
- All power connections at one central location
- Provides direct Power, Ignition Power and Timed Power
 Makes a safer electrical connection to vehicle
- Built-in Watchdog

·932-0014A / 932-0014B ·

- Trunk Side Door compartment for Dodge Charger 932-0014A to mount on Driver Side
- 932-0014B to mount on Passenger Side





D&R ELECTRONICS CO.LTD. 8820 GEORGE BOLTON PKWY. BOLTON, ONTARIO L7E 2Y4 TEL: 905-951-9997 / FAX: 905-951-0019 Toll Free: 1-800-538-7338 www.dandrelectronics.com







PL-46 LINEAR LIGHTBAR -

- New generation lightbar that combines the best features of LED technology
- Mounting kits available for most makes and models of vehicles
- Meets all applicable SAE Class 1 and California Title XIII when properly configured
- Strong Extruded aluminum frame and UV treated polycarbonate lens

Length - 22" / 35"/ 46" / 56"

Width - 13.0"

Height - 2.75" (w/o mounting feet)



MR6-8TD-R/B

MR6-8TD-R/B TRAFFIC DIRECTOR

State of the art bi-functional (warning device and arrowstick) traffic warning device, designed to be compact yet provide maximum light intensity.

MR6 LINEAR LED LIGHTS-

- The latest in LED technology
- Surface mount linear LED flashing modules ideally suited for use in directional warning
- Compact modules provide great versatility for a wide range of mounting options
- All modules are sealed, waterproof for external mounting applications
 ■ Also available installed as flush-mounted in
- Setina Push Bumper
- Multiple Flash Patterns built-in
- Dimensions:

Length - 3.25" / Width - 1.25" / Depth - 1.1"

DRCS100 SPEAKERS

- DRCS100 is one of D&R's most innovative cast 100 Watt speakers
 ■ Class A - SAE approved
- Dimensions:
- Width 6.5", Height 5.375", Depth 3.0"
- Shown mounted on Setina Pushbumper PB400AL/CHARGER



WB-CHARGER-R/B

- Rear window bar is offering protection from windows being kicked out by restrained prisoners while placed in the back seat
- Designed to fit with rear partition cages by Setina Manufacturing ■ Includes dual light module per side for side warning coverage



MR8VL-CHRGR

- LED Visor Light with MR8 LED modules
- Available with MR6 LED modules part#: MR6VL-CHRGR
- High visibility when activated
- Low profile, lightweight
- Extremely discrete and non-intrusive
- Split Red/Blue super bright LED

L12I LED INSERT

- Lamp and In-Line flasher are fully encapsulated for moisture and vibration resistance
- Includes synchronize feature for alternating and synchronous flashing of multiple lamps
- Ultra small

MINI ODYSSEY LIGHTBAR-

- Compact lightbar and arrowboard combination
- The retractable motorized arrowboard/traffic director provides superior visibility in a low profile configuration

 Full advantage of a 360 degree lightbar when in lower position
- Motorized for easy deployment
- Mounting kit included
 Meets SAE Class1 when properly configured



CONTOUR CONSOLES

- Designed to fit 2011 Dodge Charger
- Floorplate not required to install this console
- 3 types of console:
- 901-0071A contour console (allows for mounting up to 5 pieces of equipment) 901-0072A - contour console with optional swing arm LT7600
- (allows for mounting up to 4 pieces of equipment
- 901-0073A contour console with armrest

(allows for mounting up to 4 pieces of equipment)



901-0071A



LIGHT/SIREN CONTROLLERS



- Surface mount module
- Lamp and In-Line flasher are fully encapsulated for moisture and vibration resistance
- Able to synchronize in both alternating and synchronous modes
- Safe low voltage wiring
- Black or White external bezel



CA-0130

Available in 12" & 18" lengths ■ 3 Phase light intensity 1Watt LED

■ LED Maplight

■ 280° Turning Radius

■ 1 Watt Red & White LED

- 14 controlled outputs: 3@20Amps, 11@10Amps
- All control outputs are solid state relays
- Operates one or two 100W speakers
- Meets SAE J1849



- Selectable setting for flash pattern
- Input Voltage: 11 to 16 Volts DC
- Operation Temperature Ranges: -30°C to +65°C
- Standby Current: 0.05mA ± 10%

SIREN SPECS

- Operating Current: 10Amps
- Frequency Range: 700 to 1640 Hz
 Cycle rate: Wail 17 cycles/min
- Yelp 230 cycles/min Stinger - 1000 cycles/min
- Nominal Voltage Output: 52 Volts peak to peak (with 11Ω load)
- Audio Response: 100-4000 Hz ± 3dB
- Audio Power: 32 Watt
- Input Impedance:600Ω (Radio)
- Meets SAE J1849